

11-22-00

EF409652362 US

A

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Docket No. AUS9-2000-0552-US1

Assistant Commissioner for Patents
Washington, D.C. 20231

11/21/00

JC929 U.S. PTO
09/717818
11/21/00

Sir:

Transmitted herewith for filing is the patent application of Inventor(s):
Joseph Mulavelil George, Piotr KrychniakFor: **Method and System for a Generic Metadata-Based Mechanism to Migrate
Relational Data Between Databases**

Enclosed are also:

- X 28 Pages of Specification including an Abstract
- X 6 Pages of Claims
- X 8 Sheet(s) of Drawings
- X A Declaration and Power of Attorney
- X Form PTO 1595 and assignment of the invention to IBM Corporation
- X Form PTO 1449 Information Disclosure Statement
- X 8 Copies of References
- X Our return postcard

CLAIMS AS FILED

FOR	Number Filed	Number Extra	Rate	Basic Fee (\$710)
Total Claims	18	-20 = 0	X \$ 18	= \$0
Independent Claims	3	-3 = 0	X \$ 80	= \$0
Multiple Dependent Claims	0		X \$270	= \$0
Total Filing Fee				= \$710

- X Please charge \$710.00 to IBM Corporation, Deposit Account No. 09-0447.
- X The Commissioner is hereby authorized to charge payment of the following fees associated with the communication or credit any over payment to IBM Corporation, Deposit Account No. 09-0447. A duplicate copy of this sheet is enclosed.
- X Any additional filing fees required under 37CFR § 1.16.
- X Any patent application processing fees under 37CFR § 1.17.

Respectfully,

Jeffrey S. LaBaw
Reg. No. 31,638Intellectual Property Law Dept.
IBM Corporation
11400 Burnet Road 4054
Austin, Texas 75758
Telephone: (512) 823-0494

09717818-112100

JC966 U.S. PTO
11/21/00

METHOD AND SYSTEM FOR A GENERIC METADATA-BASED MECHANISM TO MIGRATE RELATIONAL DATA BETWEEN DATABASES

CROSS-REFERENCE TO RELATED APPLICATIONS

The present application is related to the following applications: Application Serial Number (Attorney Docket Number AUS000185US1), filed xx/xx/2000, titled "Apparatus and Method for Deletion of Objects From an Object-Relational System in a Customizable and Database Independent Manner"; Application Serial Number (Attorney Docket Number AUS9-2000-0551-US1), filed xx/xx/2000, titled "Method and System for an Object Model with Embedded Metadata and Mapping Information".

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to an improved data processing system and, in particular, to a method and system for using a database. Still more particularly, the present invention provides a method and system for moving data between databases.

2. Description of Related Art

Most enterprises today have large information technology (IT) infrastructures. As an enterprise expands its operations and offered services, more data is generated and gathered, and its data storage and data processing requirements also grow. In a manner similar to upgrading and replacing its computer hardware, an

[illegible]

AUS9-2000-0552-US1

enterprise may also need to update and replace the database products that serve its data storage and data processing requirements. In addition, many datasets may be regarded by an enterprise as being mission-critical and worthy of extensive backup in different forms. Hence, data is often migrated between two databases with the same, or at least very similar, schemas.

Many database tools are commercially available for migrating data between databases. However, these tools are generally proprietary and do not operate across different vendor databases.

Therefore, it would be advantageous to provide a method and system for generically migrating data from one relational database to another. It would be especially advantageous to allow the data migration to be customizable and extensible to support custom mappings.

09717818-112100

SUMMARY OF THE INVENTION

A method and system for migrating data between databases is provided. Metadata is obtained from a source database, and the metadata includes definitions for tables in the source database. The metadata is then used to determine the manner in which the data within the source database should be migrated to a target database. By structuring queries in accordance with the definitions of the tables, the metadata provides a generic determination of the structure of the data to be migrated. The dependencies among tables in the source database are also discovered, and these dependencies determine the order in which the migration operations should be performed when migrating the data. In addition, custom mapping operations may be performed during the migration operations so that the data from the source database is modified before writing the data to the target database.

BRIEF DESCRIPTION OF THE DRAWINGS

The novel features believed characteristic of the invention are set forth in the appended claims. The invention itself, further objectives, and advantages thereof, will be best understood by reference to the following detailed description when read in conjunction with the accompanying drawings, wherein:

Figure 1A depicts a typical distributed data processing system in which the present invention may be implemented;

Figure 1B depicts a typical computer architecture that may be used within a data processing system in which the present invention may be implemented;

Figure 2 is a block diagram that illustrates the relationship of typical software components within a computer system that may implement the present invention;

Figures 3A and 3B are diagrams illustrating exemplary data paths taken by requests and commands to use information stored in a relational database resident on a database server;

Figure 4 is an exemplary diagram illustrating a relational database;

Figure 5A is a diagram depicting the data flow between the database migrator, the databases, and other components;

Figure 5B is a flowchart depicting a process for migrating data between relational databases; and

AUS9-2000-0552-US1

Figures 6A-6D are a set of diagrams that provide metadata information, mapping information, an exemplary target table, and table dependency information in an XML-formatted manner for use in migrating a database.

001213 13100

DETAILED DESCRIPTION OF THE INVENTION

With reference now to the figures, **Figure 1A** depicts a typical network of data processing systems, each of which may implement the present invention. Distributed data processing system **100** contains network **101**, which is a medium that may be used to provide communications links between various devices and computers connected together within distributed data processing system **100**. Network **101** may include permanent connections, such as wire or fiber optic cables, or temporary connections made through telephone or wireless communications. In the depicted example, server **102** and server **103** are connected to network **101** along with storage unit **104**. In addition, clients **105-107** also are connected to network **101**. Clients **105-107** and servers **102-103** may be represented by a variety of computing devices, such as mainframes, personal computers, personal digital assistants (PDAs), etc. Distributed data processing system **100** may include additional servers, clients, routers, other devices, and peer-to-peer architectures that are not shown.

In the depicted example, distributed data processing system **100** may include the Internet with network **101** representing a worldwide collection of networks and gateways that use various protocols to communicate with one another, such as LDAP, TCP/IP, HTTP, etc. Of course, distributed data processing system **100** may also include a number of different types of networks, such as, for example, an intranet, a local area network (LAN), or a

09747818 4300
00000000 00000000

wide area network (WAN). For example, server 102 directly supports client 109 and network 110, which incorporates wireless communication links. Network-enabled phone 111 connects to network 110 through wireless link 112, and PDA 113 connects to network 110 through wireless link 114. Phone 111 and PDA 113 can also directly transfer data between themselves across wireless link 115 using an appropriate technology, such as Bluetooth™ wireless technology, to create so-called personal area networks or personal ad-hoc networks. In a similar manner, PDA 113 can transfer data to PDA 117 via wireless communication link 116.

With reference now to **Figure 1B**, a diagram depicts a typical computer architecture of a data processing system, such as those shown in **Figure 1A**, in which the present invention may be implemented. Data processing system **120** contains one or more central processing units (CPUs) **122** connected to internal system bus **123**, which interconnects random access memory (RAM) **124**, read-only memory **126**, and input/output adapter **128**, which supports various I/O devices, such as printer **130**, disk units **132**, or other devices not shown, such as a sound system, etc. System bus **123** also connects communication adapter **134** that provides access to communication link **136**. User interface adapter **148** connects various user devices, such as keyboard **140** and mouse **142**, or other devices not

shown, such as a touch screen, stylus, microphone, etc. Display adapter 144 connects system bus 123 to display device 146.

Those of ordinary skill in the art will appreciate that the hardware in **Figure 1B** may vary depending on the system implementation. For example, the system may have one or more processors and one or more types of non-volatile memory. Other peripheral devices may be used in addition to or in place of the hardware depicted in **Figure 1B**. In other words, one of ordinary skill in the art would not expect to find similar components or architectures within a network-enabled phone and a fully featured desktop workstation. The depicted examples are not meant to imply architectural limitations with respect to the present invention.

In addition to being able to be implemented on a variety of hardware platforms, the present invention may be implemented in a variety of software environments. A typical operating system may be used to control program execution within each data processing system. For example, one device may run a Unix™ operating system, while another device contains a simple Java™ runtime environment. A representative computer platform may include a browser, which is a well known software application for accessing hypertext documents in a variety of formats, such as graphic files, word processing files, Extensible Markup Language (XML), Hypertext Markup Language (HTML), Handheld Device Markup Language (HDML), Wireless Markup Language (WML), and various other formats and types of files. Hence, it should be noted that the distributed data processing system shown in **Figure 1A** is

AUS9-2000-0552-US1

contemplated as being fully able to support a variety of peer-to-peer subnets and peer-to-peer services.

The present invention may be implemented on a variety of hardware and software platforms, as described above. More specifically, though, the present invention is directed to providing a method and system for migrating data between databases. As background, a typical relational database is described before describing the present invention in more detail.

While the present invention will be described with reference to preferred embodiments in which Java applications are utilized, the invention is not limited to the use of the Java programming language. Rather, any programming language may be utilized with the principles of the present invention. The only requirement is that there must be some means for obtaining the structure of the relational database in the form of metadata information. For example, the present invention may be implemented using Microsoft Open Database Connectivity (ODBC). The ODBC driver provides links to such server/client database systems as Oracle and SQL Server and to desktop database systems such as dBASE and FoxPro.

The present invention may be implemented within a variety of system configurations. For example, if the system makes use of a traditional client/server application, the present invention may be implemented at the client device. If the system makes use of a three-tier application, the present invention may be implemented at a server. Furthermore, the client and server devices may be implemented as client and server processes on the same physical device. Thus, with regard to the descriptions of the preferred embodiments herein,

09-18-11 11:10

AUS9-2000-0552-US1

client and server may constitute separate remote devices or the same device operating in two separate capacities. Thus, the application tools according to the present invention may be stored in local memory, executed by a device's processor, and use the device's network connections.

With reference now to **Figure 2**, a block diagram illustrates the relationship of typical software components operating within a computer system that may implement the present invention. Java-based system **200** contains platform specific operating system **202** that provides hardware and system support to software executing on a specific hardware platform. JVM **204** is one software application that may execute in conjunction with the operating system. JVM **204** provides a Java run-time environment with the ability to execute Java application or applet **206**, which is a program, servlet, or software component written in the Java programming language. The computer system in which JVM **204** operates may be similar to data processing system **120** described above. However, JVM **204** may be implemented in dedicated hardware on a so-called Java chip, Java-on-silicon, or Java processor with an embedded picoJava core.

JVM **204** is the center of a Java run-time environment and supports all aspects of the Java environment, including its architecture, security features, mobility across networks, and platform independence. JVM **204** is a virtual computer that executes Java programs. JVM **204** is, in essence, a computer that is specified abstractly. The JVM loads class files and executes the bytecodes within them. The various Java specifications define

certain features that every JVM must implement, with some range of design choices that may depend upon the platform on which the JVM is designed to execute. For example, all JVMs must execute Java bytecodes and may use a range of techniques to execute the instructions represented by the bytecodes. A JVM may be implemented completely in software or somewhat in hardware. This flexibility allows different JVMs to be designed for mainframe computers and PDAs.

In the preferred embodiment, Java Database Connectivity (JDBC) application interfaces are used to communicate with the relational database. JDBC application interfaces are application interfaces that are used to access heterogeneous databases in a transparent manner. The Java Database Connectivity (JDBC) kit was developed for Java to allow programmers to connect to a database and query it or update it using the Structured Query Language (SQL). JDBC can be used in both Java applications and applets. These applications and applets can be implemented as a traditional client/server program, as shown in **Figure 3A**, or as a three-tier application as shown in **Figure 3B**.

With reference now to **Figures 3A and 3B**, diagrams illustrate exemplary data paths taken by requests and commands to store object-oriented data in a relational database resident on a database server. As shown in **Figure 3A**, in a traditional client/server program, client **310** uses JDBC **320** to establish a communication connection with the database server **330** using a database protocol. In a three-tier application as shown in **Figure 3B**, client **340** does not make database calls. Instead, the client

AUS9-2000-0552-US1

340 calls on a middleware layer **350** on the server that in turn makes the database queries using JDBC **360**.

The three-tier model separates the visual presentation from the business logic, i.e. the Java applications, and the raw data in the database **370**. Therefore, it becomes possible for the same data and same business rules to be accessed from multiple clients. Communication between client **340** and middleware **350** can occur by using various protocols such as HTTP (Hypertext Transport Protocol), RMI (Remote Method Invocation), and the like. Communication between middleware **350** and database server **370** occurs using JDBC **360** and a database protocol. The present invention is equally applicable to either the client/server or the three-tier structure shown in **Figures 3A** and **3B**. For purposes of illustration, it will be assumed with regard to the embodiments described herein that the traditional client/server structure is utilized.

With reference now to **Figure 4**, exemplary tables illustrate a simplified relational database in which object data is stored. A relational database can be utilized in an object-relational system, i.e. a system in which applications operate on objects which are mapped to the corresponding data representations, i.e. records, in tables of a relational database. As shown in **Figure 4**, the relational database is comprised of a plurality of tables **410-430** which are linked based on common attributes shown as columns in the tables.

Table **410** includes information identifying authors. The table **410** includes such information as the author identification, the author's name, and a uniform resource

2025 RELEASE UNDER E.O. 14176

AUS9-2000-0552-US1

locator (URL) associated with the author. The author record is a data representation of an author object that may be utilized by a Java application.

The primary key (PK) of the table **410** (AUTH_TABLE) is the author identifier, or AUTHOR_ID. The primary key is the attribute that uniquely identifies a record in the table. Thus, the AUTHOR_ID in table **410** is the primary key since multiple authors may have the same name but will have different AUTHOR_IDs.

Table **430** (BOOK_TABLE) includes information identifying books. The table **430** includes such information as the TITLE of the book, the ISBN, the PUBLISHER_ID, an associated URL, and a PRICE for the book. The primary key for the records in the table **430** is the ISBN since this attribute uniquely identifies a book in the table **430**. "ISBN" stands for "International Standard Book Number" and is a unique ten digit number assigned to each published book in many countries.

Table **420** (BOOK_AUTH_TABLE) includes information identifying book authors. The table **420** includes such information as the ISBN of the book(s) authored by the author, the author's AUTHOR_ID, and a SEQ_NO (sequence number) for the author. This information shows the authors for a specific book as well as the books authored by a specific author. It represents an intersection entity that maps the many-many relationship between authors and books. The primary key for the records in table **420** is the combination of the (Author_ID,ISBN) pair which uniquely identifies each record. In addition, table **420** includes the foreign keys AUTHOR_ID from table **410** (AUTH_TABLE) and ISBN from table **430** (BOOK_TABLE). A

001213-100

AUS9-2000-0552-US1

foreign key is a primary key of one table that is present in another table. The tables **410-420-430** are linked by way of their primary and foreign keys.

Thus, based on the primary and foreign keys of the tables **410-420-430**, the book-author object data in table **420** may not exist independently of the author object data in table **410** or the book object data in table **430**. In other words, the primary key (Author_ID) of the table **410**, i.e. a foreign key in table **420**, is a proper subset of the primary key of table **420**. Similarly, the primary key (ISBN) of the table **430** is also a proper subset of the primary key of table **420**. A foreign key is a "proper subset" of the primary key if the foreign key includes some or all of the primary keys of the table. Therefore, if an object in table **410** is to be deleted, such as the author "Adams, John", the book author object data corresponding to "Adams, John" in table **420** must be deleted also.

The JDBC kit (APIs) provides a mechanism for providing information about the structure of a relational database and its tables. For example, a user can get a list of tables in a particular relational database, the column names, types of tables, and the like. This information is known as JDBC database metadata. The metadata may also include size limitations on fields and records with the database, not-nullable constraints, etc. While the JDBC kit is utilized in the descriptions of the preferred embodiments herein, it should be appreciated by those of ordinary skill in the art that the JDBC kit is only an exemplary mechanism for providing structure information of a relational database and other mechanisms

AUS9-2000-0552-US1

may be employed without departing from the spirit and scope of the present invention. Many commercially available database products provide some manner of retrieving metadata about an implemented database.

As noted above, the present invention is operable within a variety of hardware architectures and software environments. **Figures 2-4** provide background information concerning an object-relational system. More specifically, the present invention provides a generic methodology for migrating data from one relational database to another in a manner that is customizable, extensible, and vendor-independent with respect to database application products.

With reference now to **Figure 5A**, a diagram depicts the data flow between the database migrator, the databases, and other components in accordance with a preferred embodiment of the present invention. Database migrator **502** reads data from source database **504** and copies or relocates the data into target database **506**. Database migrator **502** may be a stand-alone database application for migrating data from one database to another database. Alternatively, database migrator **502** may be a software package, a software library, an application, or an applet that is operable by other software components to perform the migration functionality. Database migrator **502** may or may not be object-oriented as required within a given system installation. In this description, since the JDBC APIs are used to obtain database metadata information, the migrator application is also implemented in Java.

CONFIDENTIAL

Databases **502** and **504** may be used to persist objects and their attributes in a well-known, object-oriented manner, such as the manner described above with respect to **Figures 3A-3B**. Alternatively, databases **502** and **504** may be simple relational databases. In addition, databases **502** and **504** may be served or supported by one or more vendor-specific database engines.

Database table dependency generator **510** discovers the type and extent of dependencies among the tables in source database **504**. In order to migrate the data in the correct sequence, the dependencies among the tables must be established, and these dependencies should be available in a programmatically-accessible format. In the preferred embodiment, the dependencies between tables can be represented using elements within an XML-formatted document, which is described in more detail further below. This dependency information can be obtained during a "first pass", i.e. a pre-processing or pre-migration phase, before the actual data migration is commenced. Alternatively, as is well known in the art, the creation of referential integrity constraints in the target database can be deferred until after all of the data has been migrated.

Database metadata generator **512** retrieves available metadata from source database **504** by querying source database **504** and storing or caching the metadata. The data migration of the present invention is guided by using the metadata for each table in source database **504**. This metadata information comprises definitions of each table, the columns in each table, the type definitions of those columns, and any other constraints related to the

001213 01347250

tables. This metadata information can also be gathered during a pre-migration phase and then stored or cached in an intermediate format. In the preferred embodiment, the metadata information can be represented using elements within an XML-formatted document, which is described in more detail further below.

These data definitions in the metadata provide a structure for a query operation on the source database. For example, the source database may be accessible through a database application, database engine, database server, etc., that supports SQL (Structured Query Language). After parsing the metadata, one can use the data type information, etc., to construct SQL commands that are issued to the database engine to retrieve the data stored within the source database. These SQL commands are executed using command execution calls in the JDBC API.

The metadata provides a clear structure for the source database tables and thus enables generic read capabilities. Referring ahead to **Figure 6A**, the figure shows the metadata information for the table AUTH_TABLE (410). The metadata shows that there are 4 fields in the table and that the fields are all strings, as indicated by the VARCHAR2 type. Thus, the runtime operation of the reading component can interpret this metadata information generically to determine that each record in the AUTH_TABLE comprises 4 string fields and must be read accordingly.

Referring again to **Figure 5A**, data mapping customization component 514 performs any optional custom transformations of data by applying mapping

transformations after data is read from source database 504 but before data is written to target database 506. The optional transformations are established before any data migration is performed. The custom transformations can be stored in a mapping repository and retrieved as needed. In the preferred embodiment, the customization information can be represented using elements within an XML-formatted document, which is described in more detail further below.

With reference now to **Figure 5B**, a flowchart depicts a process for migrating data between relational databases in accordance with a preferred embodiment of the present invention. The process, which may be implemented within a system similar to that shown in **Figure 5A**, begins by reading or obtaining the metadata information from the relational database (step **550**). Information about the dependencies among the tables in the source database is

then obtained by using the metadata information read in step 550 in conjunction with optionally defined heuristics (step 552). The dependencies can be represented in an intermediate format for subsequent use to control the order of migrating the tables in the source database. The metadata information obtained in step 550 can then be used to identify and organize metadata information about each table in the source database (step 554). It should be noted that step 552 or step 554 can happen in any order, but step 550 must be performed before either step 552 or step 554. The metadata information can also be represented in an intermediate format for subsequent use to control the manner in which each data item or data chunk is migrated.

The order of migration of data should follow a breadth-first-search (BFS) traversal of the dependency tree, which ensures that tables without any dependencies are migrated first, thereby preventing the occurrence of any referential integrity constraint violations when data in dependent tables is written. In other words, when the data in a table is migrated, the BFS traversal order ensures that any data that needs to exist for the data in the current table to be written has already been migrated. Because the metadata from each table is

AUS9-2000-0552-US1

available, having been acquired in step 554, it is possible to interpret the data read from the database in a generic manner. The process continues when a row of data from a table stored within the source database is then retrieved (step 556) in accordance with the previously compiled dependency information.

Any predetermined custom transformations, i.e. optionally defined heuristics, between the source tables and the target tables are then applied to the data (step 558). The row of data is then written to a corresponding table in the target database (step 560). Database commands may be issued as necessary to write the data to the target database depending upon the type of target database. For example, assuming that the target database supports SQL, SQL statements may be issued by the database migrator component to the target database engine or server to write the data into the target database. Similar to the read operation on the source database, the metadata information allows the write operation logic to be generic. For example, to migrate data from the AUTH_TABLE table shown in **Figure 4**, we need to write 4 string fields for each record as defined in the metadata derived for the AUTH_TABLE table.

A determination is then made as to whether or not there are any more rows of data for the table that is currently being migrated (step 562). If so, then the process branches back to step 556 to migrate more data. If the current table has been completely migrated, then a determination is made as to whether or not any more tables of data have not yet been migrated from the source database to the target database (step 564). If so, then

001213 1100

AUS9-2000-0552-US1

the process branches back to step 555 to migrate another table. The next table to be migrated is chosen based on the dependency information obtained in step 552.

Otherwise, the entire source database has been migrated, and the process is complete.

With reference now to **Figures 6A-6D**, a set of diagrams provide metadata information, mapping information, an exemplary target table, and table dependency information that may be used in accordance with a preferred embodiment of the present invention. The examples shown in **Figures 6A-6C** continue the example shown in **Figure 4**.

Figure 6A shows metadata information for table 410 in **Figure 4** that has been retrieved from the database. Depending upon the implementation and the size and number of tables, the metadata information may be more detailed. In this example, the metadata information has been formatted as an XML document. Each table entity contains elements and sub-elements with information on each record field or column within the table, such as the name of the field, its position, and its data type.

Metadata information 610 may also contain database constraints, size limits, and other potential database limitations to be used when migrating data between databases. In metadata information 610, each record field has an associated constraint "Nullable" that indicates whether or not a field can be "NULL" when stored within the database. In addition, each field element has a sub-element "Length" that indicates the maximum length of the data that may be stored within the database field, thereby providing a type of size constraint. Other

AUS9-2000-0552-US1

constraints or limitations may be shown in a similar manner if necessary for a particular database implementation.

Figure 6B shows an example of custom mapping information that may be stored using an XML format, although other data formats could be used. Mapping information **620** defines how custom transformations can be applied to the data that is being migrated between the corresponding tables in the databases. This information is generated, either manually or automatically, during the development of the corresponding database schemas, i.e. it is statically defined. The mapping record shown in **Figure 6B** is the simplified case of a single table mapping to a single table. In this case, the structure of the source and target tables are the same, and only the names of the fields and the table are different.

Depending upon the desired implementation, it is possible for more complex transformations to be applied when mapping data between multiple tables, and the mapping record would reflect this accordingly. For example, the target AUTH_TABLE might now have a new field AUTHOR_AGENT that indicates the name of the authors agent. A simple mapping transformation could specify that the value of this field in the target table should be set to "UNKNOWN". A more sophisticated mapping transformation could specify that all authors with AUTH_IDs from "A" to "M" should have a value of "JOE SMITH" in the AUTHOR_AGENT field and all others should be given a value of "DAVID JONES".

In **Figure 4**, author table **410** has columns "Author_ID", "Name", "URL", and "Description" as fields within each record in the table. Each attribute within

AUS9-2000-0552-US1

the author table has a corresponding entry within the mapping record in **Figure 6B** which provides the name of the source database field as indicated by the "SourceFieldName" XML element. Associated with each source database field is semantic information indicating whether or not the field is truncatable. The target field name in the target database is identified by the "TargetFieldName" XML element, which also specifies the data type of that attribute.

In XML terminology, each "MappingRecord" element associates a particular table in the target database, as indicated by the "TargetTableName" property associated with each "MappingRecord", with a table in the source database, as indicated by the "SourceTableName" element. Each "MappingRecord" entity has one "Field" element for each field in the target table with an element property indicating its relative "Position". Each "Field" element then has subelements linking each target field "TargetFieldName" with a source database column "SourceFieldName" and associated semantic information.

By comparing **Figures 6A-6B**, one can see that the names of the fields in a particular table in the source database, as retrieved in metadata information **610**, and the names of the fields in the target database are mapped together by mapping information **620**. With the associations between the source database fields and the target database fields provided by the mapping records, custom transformations can be easily associated with the appropriate tables.

In the example shown in **Figure 6B**, the "MappingRecord" entity has one "Field" element,

"T_LOCATION", for an additional field in the target table which does not have a corresponding field in the source table. The name of the source field has been left empty, and a default property value of "UNKNOWN" has been specified as the value that should be assigned to the field in the target table when a source table is migrated.

Figure 6C shows a target table with a similar structure to the source table shown in **Figure 4** except that target table **630** has an additional field, "T_LOCATION", that would have a data value set to "UNKNOWN" the data migration operation as specified by the mapping record shown in **Figure 6B**.

As an alternative method of setting a default value while using an XML-formatted file, a function may be defined within the database migrator component such that any field of type "string" that has an empty element is set equal to "UNKNOWN". More complex functions could be defined as necessary.

Although the examples show custom mapping operations implemented using an XML-formatted document, custom mapping operations may be implemented in any appropriate manner. The following example is shown using pseudo-code in a rule-based language, although other programmatic formats could be used. For example, the following rule could be used:

```
IF (substring('loc', <field_name>)
    THEN default(<field name> = "UNKNOWN").
```

This rule indicates that if the field name (or column name) that is currently being processed contains the substring "loc", then the associated database field that is currently being processed is probably a location

field, and the current data for the field should be set to a default value.

The advantages of the present invention should be apparent in view of the detailed description of the invention that is provided above. In the prior art, specialized database tools were required to migrate data from one database to another database.

In the present invention, metadata is obtained from a source database and used to determine the manner in which the data within the source database should be migrated to a target database. The metadata provides a

mechanism for structuring queries to retrieve the data within the source database in a generic manner, thereby providing a generic determination of the structure of the data to be migrated. The dependencies among tables in the source database are discovered, thereby providing an order to the migration operations to be performed when migrating the data. This order ensures that the data can be migrated correctly in the presence of referential integrity (foreign key) constraints. In addition, custom mapping operations may be performed during the migration operations so that the data from the source database is modified before writing the data to the target database.

It is important to note that while the present invention has been described in the context of a fully functioning data processing system, those of ordinary skill in the art will appreciate that the processes of the present invention are capable of being distributed in the form of instructions in a computer readable medium and a variety of other forms, regardless of the particular type of signal bearing media actually used to carry out the distribution. Examples of computer readable media include media such as EPROM, ROM, tape, paper, floppy disc, hard disk drive, RAM, and CD-ROMs and transmission-type media, such as digital and analog communications links.

The description of the present invention has been presented for purposes of illustration but is not intended to be exhaustive or limited to the disclosed embodiments. Many modifications and variations will be apparent to those of ordinary skill in the art. The embodiments were chosen to explain the principles of the invention and its practical applications and to enable

others of ordinary skill in the art to understand the invention in order to implement various embodiments with various modifications as might be suited to other contemplated uses.

What is claimed is:

1. A method for migrating data between a first database and a second database, the method comprising the steps of:

retrieving metadata from the first database, wherein the metadata includes definitions for tables in the first database;

writing data to the second database using a plurality of write operations, wherein the write operations are in an order indicated by the determined set of dependencies.

2. The method of claim 1 further comprising:
storing the determined set of dependencies using
markup language to identify table dependencies.

3. The method of claim 1 further comprising:
storing the retrieved metadata using markup language
to identify the retrieved metadata.

7. An apparatus for migrating data between a first database and a second database, the apparatus comprising:

retrieving means for retrieving metadata from the first database, wherein the metadata includes definitions for tables in the first database;

writing means for writing data to the second database using a plurality of write operations, wherein the write operations are in an order indicated by the determined set of dependencies.

first storing means for storing the determined set of dependencies using markup language to identify table dependencies.

second storing means for storing the retrieved metadata using markup language to identify the retrieved metadata.

AUS9-2000-0552-US1

10. The apparatus of claim 7 further comprising:

performing means for performing a predetermined modification operation on the data read from the tables in the first database prior to a write operation to the second database.

11. The apparatus of claim 10 further comprising:

third storing means for storing the predetermined modification operation using markup language to identify the predetermined modification operation.

12. The apparatus of claim 7 wherein the first database and the second database have dissimilar schemas.

09717818-112100

AUS9-2000-0552-US1

13. A computer program product in a computer readable medium for use in a data processing system for migrating data between a first database and a second database, the computer program product comprising:

instructions for determining a set of dependencies among a plurality of tables in the first database;

instructions for retrieving metadata from the first database, wherein the metadata includes definitions for tables in the first database;

instructions for reading data from tables in the first database using a plurality of read operations, wherein the read operations are structured in accordance with the retrieved metadata, and wherein the read operations are in an order indicated by the determined set of dependencies; and

instructions for writing data to the second database using a plurality of write operations, wherein the write operations are in an order indicated by the determined set of dependencies.

14. The computer program product of claim 13 further comprising:

instructions for storing the determined set of dependencies using markup language to identify table dependencies.

15. The computer program product of claim 13 further comprising:

instructions for storing the retrieved metadata using markup language to identify the retrieved metadata.

0971818-1100

AUS9-2000-0552-US1

16. The computer program product of claim 13 further comprising:

instructions for performing a predetermined modification operation on the data read from the tables in the first database prior to a write operation to the second database.

17. The computer program product of claim 16 further comprising:

instructions for storing the predetermined modification operation using markup language to identify the predetermined modification operation.


18. The computer program product of claim 13 wherein the first database and the second database have dissimilar schemas.

0974338-1300

ABSTRACT OF THE DISCLOSURE**METHOD AND SYSTEM FOR A GENERIC METADATA-BASED MECHANISM
TO MIGRATE RELATIONAL DATA BETWEEN DATABASES**

A method and system for migrating data between databases is provided. Metadata is obtained from a source database and used to determine the manner in which the data within the source database should be migrated to a target database. The metadata provides a mechanism for structuring queries to retrieve the data within the source database in a generic manner, thereby providing a generic determination of the structure of the data to be migrated. The dependencies among tables in the source database are discovered, thereby providing an order to the migration operations to be performed when migrating the data. This order ensures that the data can be migrated correctly in the presence of referential integrity (foreign key) constraints. In addition, custom mapping operations may be performed during the migration operations so that the data from the source database is modified before writing the data to the target database.

CONFIDENTIAL



001211 213450


Prior Art
Figure 1A

The diagram illustrates a computer system 120. A central vertical bus 123 connects several internal components: a stack of CPUs (122), RAM (124), ROM (126), an I/O Adapter (128), and a Communication Adapter (134). The I/O Adapter (128) is connected to a Printer (130) and a Disk (132). The Communication Adapter (134) is connected to a bidirectional communication line 136. A Display Adapter (144) is connected to the bus 123 and a Display (146). A User Interface Adapter (148) is also connected to the bus 123 and manages a Keyboard (140) and a Mouse (142).

120


Prior Art

Figure 2



Prior Art

Figure 3A



Prior Art

Figure 3B

AUTHOR_ID (PK)	NAME	URL	DESCRIPTION
ADAM APON	ADAMS, JOHN APONE, KEVIN	HTTP://... HTTP://...	"This author received an IEEE ..." "After spending ten years in ..."
.	.	.	.
.	.	.	.
.	.	.	.

Y

AUTH_TABLE	
------------	--

ISBN (PK)	AUTHOR_ID (PK)	SEQ_NO
0-08-882-111-4	ADAM	1
0-07-456-432-1	APON	4
.	.	.
.	.	.
.	.	.

BOOK_AUTH_TABLE

ISBN (PK)	TITLE	PUBLISHER_ID	URL	PRICE
0-08-882-111-4	BEYOND THE ARTIC	00989	HTTP://...	27.95
0-07-456-432-1	GUIDE TO JAVA	01432	HTTP://...	15.00
.
.
.

Figure 4




Figure 5A




Figure 5B

610

```

<Table name="AUTH_TABLE" numattributes="4">
  <PrimaryKey>
    <Field name="AUTHOR_ID" pos="1">
      <Type> VARCHAR2 </Type>
      <Nullable> FALSE </Nullable>
      <Length> 20 </Length>
    </Field>
  </PrimaryKey>
  <Field name="NAME" pos="2">
    <Type> VARCHAR2 </Type>
    <Nullable> FALSE </Nullable>
    <Length> 40 </Length>
  </Field>
  <Field name="URL" pos="3">
    <Type> VARCHAR2 </Type>
    <Nullable> FALSE </Nullable>
    <Length> 1024 </Length>
  </Field>
  <Field name="DESCRIPTION" pos="4">
    <Type> VARCHAR2 </Type>
    <Nullable> FALSE </Nullable>
    <Length> 512 </Length>
  </Field>
</Table>

```

Figure 6A

620

```

<MappingRecord TargetTablename="T_AUTH_TABLE" >
  <SourceTableName> AUTH_TABLE </SourceTableName>
  <Field position="1">
    <TargetFieldName type= "String"> T_AUTHOR_ID </TargetFieldName>
    <SourceFieldName> AUTHOR_ID </SourceFieldName>
    <Truncatable> NO </Truncatable>
  </Field>
  <Field position="2">
    <TargetFieldName type= "String"> T_AUTHOR_NAME </TargetFieldName>
    <SourceFieldName> NAME </SourceFieldName>
    <Truncatable> NO </Truncatable>
  </Field>
  <Field position="3">
    <TargetFieldName type= "String"> T_URL </ClassField>
    <SourceFieldName> URL </SourceFieldName>
    <Truncatable> NO </Truncatable>
  </Field>
  <Field position="4">
    <TargetFieldName type= "String"> T_DESCRIPTION </TargetFieldName>
    <SourceFieldName> DESCRIPTION </SourceFieldName>
    <Truncatable> YES </Truncatable>
  </Field>
  <Field position="5" default="Unknown">
    <TargetFieldName type= "String"> T_LOCATION </TargetFieldName>
    <SourceFieldName></SourceFieldName>
  </Field>
</MappingRecord>

```

Figure 6B

630

T_AUTHOR_ID	T_AUTHOR_NAME	T_URL	T_DESCRIPTION	T_LOCATION
AUTH_TABLE				

Figure 6C

```

<Table Name="AUTH_TABLE">
  <PrimaryKey>
    <Field name="AUTHOR_ID" type="VARCHAR2"></Field>
  </PrimaryKey>
  <Dependent Name="BOOK_AUTH_TABLE">
    <ForeignKey>
      <Attribute position="1">
        <Parent>AUTHOR_ID</Parent>
        <Child>AUTHOR_ID</Child>
      </Attribute>
    </ForeignKey>
  </Dependent>
</Table>

<Table Name="BOOK_AUTH_TABLE">
  <PrimaryKey>
    <Field name="ISBN" type="VARCHAR2"></Field>
  </PrimaryKey>
  <Dependent Name="BOOK_TABLE">
    <ForeignKey>
      <Attribute position="1">
        <Parent>ISBN</Parent>
        <Child>ISBN</Child>
      </Attribute>
    </ForeignKey>
  </Dependent>
</Table>

<Table Name="BOOK_TABLE">
  <PrimaryKey>
    <Field name="ISBN" type="VARCHAR2"></Field>
  </PrimaryKey>
</Table>

```

00T3T"BT3&T&60

Figure 6B

DECLARATION AND POWER OF ATTORNEY FOR PATENT APPLICATION

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name;

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

METHOD AND SYSTEM FOR A GENERIC METADATA-BASED MECHANISM TO MIGRATE RELATIONAL DATA BETWEEN DATABASES

the specification of which (check one)

X is attached hereto.

— was filed on _____
as Application Serial No. _____
and was amended on _____
(if applicable)

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to the patentability of this application in accordance with Title 37, Code of Federal Regulations, §1.56.

I hereby claim foreign priority benefits under Title 35, United States Code, §119 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:

Prior Foreign Application(s):

Priority Claimed

____ Yes ____ No

I hereby claim the benefit under Title 35, United States Code, §120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United

States application in the manner provided by the first paragraph of Title 35, United States Code, §112, I acknowledge the duty to disclose information material to the patentability of this application as defined in Title 37, Code of Federal Regulations, §1.56 which occurred between the filing date of the prior application and the national or PCT international filing date of this application:

(Application Serial #)	(Filing Date)	(Status)
------------------------	---------------	----------

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorneys and/or agents to prosecute this application and transact all business in the Patent and Trademark Office connected therewith:

John W. Henderson, Jr., Reg. No. 26,907; James H. Barksdale, Jr., Reg. No. 24,091; Thomas E. Tyson, Reg. No. 28,543; Robert M. Carwell, Reg. No. 28,499; Jeffrey S. LaBaw, Reg. No. 31,633; Douglas H. Lefevre, Reg. No. 26,193; Casimer K. Salys, Reg. No. 28,900; David A. Mims, Jr., Reg. 32,708; Volel Emile, Reg. No. 39,969; Leslie A. Van Leeuwen, Reg. No. 42,196; Christopher A. Hughes, Reg. No. 26,914; Edward A. Pennington, Reg. No. 32,588; John E. Hoel, Reg. No. 26,279; Joseph C. Redmond, Jr., Reg. No. 18,753; Marilyn S. Dawkins, Reg. No. 31,140; Mark E. McBurney, Reg. No. 33,114; Cynthia S. Byrd, Reg. No. 39,365; and Joseph R. Burwell, Reg. No. 44,468.

Send correspondence to: Joseph R. Burwell
Law Office of Joseph R. Burwell
P.O. Box 28022
Austin, Texas 78755-8022

and telephone calls to: (512) 502-9448
and faxes to: (512) 597-1218.

FULL NAME OF SOLE OR FIRST INVENTOR: Joseph Mulavelil George

INVENTOR SIGNATURE: 

DATE: 11/20/2000

RESIDENCE: Austin, Texas

CITIZENSHIP: India

POST OFFICE ADDRESS: 3456 N. Hills Dr. #201
Austin, TX 78731

001211-21327260

DOCKET NUMBER: AUS9-2000-0552-US1

FULL NAME OF SECOND INVENTOR: Piotr Krychniak

INVENTOR SIGNATURE: Piotr Krychniak

DATE: 11/20/2000

RESIDENCE: Austin, Texas

CITIZENSHIP: Poland

POST OFFICE ADDRESS: 12805 Lantana Ridge Court
Austin, TX 78732